



USB3.0

UT02	1000±30
UT03	2000±30
UT04	3000±50

USB3.0 AM	USB3.0 BM	COLOR
1	1	RED(PWR)
2	2	WHITE(UTP_D-)
3	3	GREEN(UTP_D+)
4	4	BLACK(GND_PWRnt)
5	5	YELLOW(SDP1-)
6	6	BLUE(SDP1+)
7	7	DRAIN(SDP1_Drain) (SDP2_Drain)
8	8	ORANGE(SDP2-)
9	9	PURPLE(SDP2+)
SHELL	SHELL	Braid

ELECTRICAL PROPERTIES:

- 100% OPEN SHORT MIS-WIRE TEST
- Contact Resistance:10ohm
- Insulation Resistance:5Mega ohm
- Hipot test:DC 300V/10ms

4	55P PVC MOLD BLUE IN COLOR	1	pcs
3	USB3.0 B TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	1	pcs
2	USB3.0 A TYPE MALE SHELL PLATED:NICKEL CONTACT:G/F	1	pcs
1	UL20276 (1P*28#+D+AL+Mya1r)*2C+1P*28#+2C*28#+AL+B DD:5.5±0.15mm BLUE IN COLOR	1	pcs
DESCRIPTION		Q'TY	UNIT

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	+5°
0.	+0.5
.0	+0.3
.00	+0.2
SCALE:	NONE
UNIT:	mm

DRAWN NAME: 競捷-UTXX

REV.	DESCRIPTION	DATE	APPROVED	SIZE	REV.	FILE NAME
A		09/06/20	GUDQING	A4	A	